

Your configuration



Your configuration code is

M1.P.0.1.0.0

The transmission of the configuration code is an important piece of information for identifying your desired variant both in the quotation phase and in the order phase.

Selection

Housing length [mm]	190.5
Housing diameter [mm]	90

Technical data

Description	∅	∅
	90mm	140mm
Avg. Speed ??[min-1]	200	150
Max. Speed ??[min-1]	400	300
Protection class according to IEC 60529	IP 50	
Operating temperatur [°C]	-20 to +70	
Lifetime [Mio. U]	50	
Current load [A]	Max. 63	
Voltage load [V AC]	Max. 630	
Cablelength [m]	3	

Quantity	Name	Description	Width	V	A	Ways
1	Massebahn Dummy	Is used instead of an earth protection	1	-	0	1
1	Ethernet (Module P)	Ethernet 100Base-TX. Ethernet + 4 signals (30V/3A). Available for every ethernet based protocol.	1	30	3	Ethernet + 4

Position	Name	Description	Width	Channels	Cross section	Pressure	Medium	Connections
Front	Media rotary joint (1-channel)	the usage of a media rotary joint increases the torque of the overall system		1	MIA 1 --> 6 mm MIA 2 --> 12,7 mm	air 10 bar / liquids 70 bar	air, water, oil	MIA 1 --> G 1/4" MIA 2 -- > G 1/2"

Currentplan



Drawing



